

## **Excellence in Cryogenics**

709 City Center Blvd, B-118 Newport News, VA 23606 \*\* USA Tel: +757 833 1011 / 800-8-KELVIN info@kelvinic.com / www.kelvinic.com



M280X2 industrial model without enclosure

## Features

PLC and Touch Screen
One-button with Auto-Start
Fully Automatic
Remote PC via Internet
One Year from Installation
Life on Software & Instruments
Double Redundancy
Dry Scroll Type

## M280X2 Liquid Nitrogen Generator

Fully assembled and tested COMPLETE Liquid Nitrogen Generator being fully automatic producing  $LN_2$  24-7 without operator intervention. A 300 liter vacuum insulated Stainless Steel tank stores the daily production of 100 liters. Integrated within the enclosure are an oil-free scroll air compressor and PSA GN<sub>2</sub> generator. Touch Screen (HMI) and PLC controls provide for reliable and safe operation. With the push of one button,  $LN_2$  is delivered to the customer's tank and **as easy as decanting tap water.** 

## Specifications

' **F** 

Storage Capacity:	300 liters
Peak Production:	115 liters per day
Standard Production:	100 lpd at 60 Hz
Purity:	>99.5% with 99.9%, peak
Dimensions:	117 <sup>w</sup> x 198 <sup>D</sup> x 221 <sup>H</sup> cm
Empty Weight:	985 kg
Environment:	Indoor our Outdoor
Certifications:	CE, ASME Sec, VIII
Utilities	
Air Water:	7T of Air Handling Load
Power for USA:	208 VAC, 3୭, 60 Hz, 100A
	480 VAC, 3୭, 60 Hz, 45A
Power for International:	400 VAC, 3୭, 50 Hz, 45A
Options	
Chiller for Cooling:	10T Automatic Recirculator
V.J. Transfer Line:	2.5 meter long

On-Site Installation: By KIC Service Engineers



Similar M280X3 outdoor model with enclosure

Many options and features are available to meet the customer's application and environmental conditions. Please consult with the KIC engineers regarding previous experience and custom designs.

Distributed and Supported by: